

511302-1R REVISION G ABOVE THE BILL OF MATERIAL, DISREGARD "FLIGHT CRITICAL ITEM".

DISREGARD NOTE 1, IN LIEU THEREOF THE FOLLOWING SHALL APPLY:
METAL STAMP NAWC CAGE CODE-PART NUMBER AND CONTRACT NUMBER ADJACENT TO STAMP OF CONNECTOR IN ACCORDANCE WITH MIL-STD-130.

IN NOTE 4, A-A-59313 (SUPERSEDING "MIL-T-22361").

504657-4 REVISION T IN NOTE 4, SAE AMS-QQ-C-320 (SUPERSEDING "QQ-C-320").

DISREGARD NOTE 6, IN LIEU THEREOF THE FOLLOWING SHALL APPLY:
HEAT TREAT IN ACCORDANCE WITH SAE AMS2759/1 SO THAT FINISHED PART HAS A HARDNESS OF 34 HRC TO 38 HRC. (150,000 PSI).

IN NOTE 8, NAWC CAGE CODE-PART NO. (SUPERSEDING "NAWC P/N") AND ADD "IN ACCORDANCE WITH MIL-STD-130".

IN NOTE 11, DISREGARD "OR DRY" AND DISREGARD "WITH EITHER FLUORESCENT OR NON-FLUORESCENT PARTICLES".

IN NOTE 13, ASME Y14.5M-1982 (SUPERSEDING "ASME Y14.5").

613864-1R REVISION L IN THE BILL OF MATERIAL, ACROSS FROM INSERT, SCREW, LOCKING, MS21209F5-15, ADD NASM21209 TO THE SPECIFICATION BLOCK.

IN NOTE 8, DISREGARD "INDICATIONS GREATER THAN .063 ARE NOT ACCEPTABLE".

IN NOTE 10, NAWC CAGE CODE-PART NO. AND CONTRACT NO. (SUPERSEDING "NAWC PART NO., CONTRACT NO., AND DESIGN ACTIVITY CODE IDENT. NO.").

IN NOTE 13, ASQ Q9001 (SUPERSEDING "ANSI/ASQC-Q92").

IN FIELD OF DRAWING NASM33537 (SUPERSEDING "MS33537").

NATIONAL AEROSPACE STANDARDS:

NAS517 REVISION 4

NASM21209 REVISION NONE -----

NASM33537 REVISION NONE -----

NOTE 1: WHERE NAVAL AIR ENGINEERING CENTER MATERIAL AND PROCESS REQUIREMENTS (MPR'S) AND NAEC-ENG REPORTS ARE REFERENCED, THE MPR'S AND REPORTS SHALL PREVAIL OVER ANY OTHER SPECIFICATIONS CITED. THE FOLLOWING IS A LIST OF MPR'S AND REPORTS THAT ARE REQUIRED AND APPLY:

MPR 10 REVISION D

WHERE MPR 10 IS REFERENCED, THE FOLLOWING SHALL APPLY: PARA. 9, ASTM E1444 (SUPERSEDING "MIL-STD-1949") AND PARTS MUST MEET THE REQUIREMENTS OF MIL-STD-2035 (SUPERSEDING "PARTS SHALL MEET THE

04-R-P437

PS 1 of 2

NOTE 1:
(CONT'D)

REQUIREMENTS OF NAVSEA 0900-LP-003-8000 FOR WROUGHT MATERIALS"); PARA. 10, ASTM E8 (SUPERSEDING "FEDERAL TEST METHOD STD. NO. 151"); ASTM E23 (SUPERSEDING "FEDERAL TEST METHOD STD. NO. 151"); PARA. 11, ASTM A751 (SUPERSEDING "FEDERAL TEST METHOD STD. NO. 151") AND PARA. 12, CODE 4.8.1.4 (SUPERSEDING "CODE 51234").

MPR 1223 REVISION B

WHERE MPR 1223 IS REFERENCED, THE FOLLOWING SHALL APPLY: PARA. 3.2, SAE J1993 (SUPERSEDING "MIL-S-851, TYPE I"). IN PARA'S 3.1 AND 3.3, A-A-59316 (SUPERSEDING "MIL-A-21380").

NAEC-ENG-6518 REVISION BK

THE FOLLOWING CHANGE SHALL APPLY THROUGHOUT REPORT: NAWC PART NO. (SUPERSEDING "NAEC PART NO.").

NOTE 2:

WHERE REFERENCED ON DRAWING, THE FOLLOWING SHALL APPLY:

ASME Y14.100 (SUPERSEDING "MIL-STD-100").